

High Speed Side-Seal Model for Food (Seafood and Meat Packing) Industries

■ **High Speed**

The high-speed sealing head can strap up to 50 bundles without sacrificing any strap tension.

■ **Easy Strap Loading**

RQ7000M equips the self-loading system. The strap threading is almost automatic.

■ **Quick Heater**

The RQ7000M is ready to operate in less than 20 second. Designed to ensure a high seal joint.

■ **Built To Last**

Permanently lubricated mechanisms, side-seal design and fully enclosed cabinet protect the machine from saltwater runoff, oil and dust.

■ **Moisture Protection**

With a stainless steel body and parts made of water-resistant materials such as stainless steel and aluminum, the RQ7000M defies rust and corrosion even in harsh environments. This moisture protection is reinforced at the bottom of the body which has greater exposure to moisture than other parts of the machines.

■ **Self-Correcting Technology**

If the RQ7000M is operated accidentally without a package, the strap will form a small loop which will be automatically ejected from the sealing unit leaving the machine ready for the next cycle.



■ **Standard Specifications**

Dimension	Width	1580mm	62-3/16 in.
	Height	1772mm	69-3/4 in.
	Depth	664mm	26-1/8 in.
	Weight	220kg	480 lbs
Table Height		624, 642, or 664mm	24-9/16, 25-5/16 ,26-1/8 in.
Arch Size		W700 x H650mm	W27-1/2 x H25 in.
Package Size	Max	W680 x H500mm	W26-11/16 x H19-11/16 in.
	Min	W30 x H80mm	W1-1/4 x H3-1/8 in.
Joint / Strap / Coil		Heat Seal / Polypropylene / ID200xOD450xW200mm	Heat Seal / Polypropylene / ID8xOD18xW8 in.
Strap Width		5,6,9,12mm	1/4,3/8,1/2 in.
Strap Tension		Max.690N (70kg) 150mm Stroke	Max.155lbs 5-7/8 in. Stroke
Speed		1.2 sec./strap 50 straps per min.	
Power Supply		200,220,240,380,400,415V 3 phase 50/60Hz 0.69KVA	